

## BRB 60

*EP Moly Grease For Heavy loads*

### Benefits :

- Withstands extreme pressure and heavy loads.
- Good shear stability. For rough operating conditions.
- Reduces friction and wear and thereby minimizes maintenance costs.
- Provides adequate rust protection to bearing surfaces.
- MoS<sub>2</sub> provides solid lubricating film which extends re-lubrication period.
- Wide range operating temperature band.
- Good resistance to oxidation and hot & cold water.

### Applications :

- For all types of anti-friction and sleeve bearings.
- Rolling Mills, agriculture machinery and mining.
- Universal joints, splined shafts, springs and sliding mechanism.
- Transport installations & material handling systems.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Smooth
Colour	Visual	–	Greyish Black
Base [Thickener]	–	–	Lithium
Base Oil	–	–	Mineral
NLGI Grade	–	–	# 2
Worked Penetration	ASTM D-217	0.1 mm	265 - 295
Dropping Point	ASTM D-566	°C	+180
Four Ball Weld Load	ASTM D-2596	N	3600
Four Ball Wear Scar	ASTM D-2266	mm	0.7
Copper Strip Corrosion Test	ASTM D-4048	rating	1a
Operating Temperature Range	–	°C	-20/+150

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**Anand Engineers Pvt Ltd.** 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093, INDIA.

Tel : +91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com