

## Chuck Paste 2950

*High Performance Chuck Grease*

### Benefits :

- Long term lubrication
- Contains chosen solid lubricants with a combination of additives.
- Low co-efficient of friction.
- Good clamping forces.
- Capable of withstanding jerks and heavy loads.
- Avoids fretting corrosion.
- Lubrication suitable in humid environment.
- Good adherence to metallic surfaces.
- Highly economical as the product has wide area coverage.
- Chemical resistant. Also has good resistance to steam, water and water based coolants.

### Applications :

- As assembly lubrication paste.
- For CNC & other machine tools and chuck jaws.
- For frictional and sliding surfaces.
- For lubricating of areas in filing, labeling, packaging machines, reciprocatory action sieves etc. where high level vibrating stresses are encountered.

Characteristics	Test method	Unit	Specifications
Appearance	Visual	-	Smooth Paste
Colour	Visual	-	Yellowish
Soap	-	-	Special complex
NLGI Grade	-	-	# 2
Worked Penetration	ASTM D-217	0.1 mm	265 – 295
Dropping Point	ASTM D-2265	°C	> 240
Four Ball Welded Load	ASTM D-2596	N	4000
Friction Value	*CTM	-	< 0.1
Operating Temperature Range	-	°C	-20 /+150

\*CTM=Corporate Test Method

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.3 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

CONTROLLED COPY