

Long Life 2 Plus

*High Performance Long-term
Lubricating Grease*

Benefits :

- Capable of carrying high loads.
- High base oil viscosity.
- Extended re-lubrication periods.
- Guards against corrosion.
- High adhesion to metal substrate.
- Fortified with solid lubricants.
- Moisture resistant.
- Chosen EP and corrosion inhibiting additives.
- Resists fretting corrosion and brineling.

Applications :

- For high load & slow to medium-fast movements metal to metal lubrication.
- For lubrication of various types of anti-friction bearings.
- Earth moving equipment, conveyors, cables, tractors, trucks, transportation equipment and material handling systems.
- Universal joints, splined shafts, and sliding mechanism.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Smooth, tacky
Colour	Visual	–	Black
Base [Thickener]	–	–	Lithium Complex
Base Oil	–	–	Mineral
Base Oil Viscosity @ 40°C	ASTM D-445	cSt	150
NLGI Grade	–	–	# 2
Worked Penetration	ASTM D-217	0.1 mm	265 – 295
Dropping Point	ASTM D-2265	°C	+180
Water Washout @ 80°C, wt. loss	ASTM D-1264	%	< 5
Four Ball Weld Load	ASTM D-2596	N	3800
Four Ball Wear Scar	ASTM D-2266	mm	0.8
Copper Strip Corrosion Test	ASTM D-4048	rating	1a
Operating Temperature Range	–	°C	-20/+150

MSDS available on request.

Due to continual up gradation of products above data is subject to change without notice

[REV.3 / 01.01.14]

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com