

Benefits :

- Extreme pressure additives provide high load carrying capacity.
- Excellent pumpability.
- Long term lubrication for bearings.
- Greases stay in place in heavily loaded condition.
- Resist water washout.
- Provide adequate rust protection.
- Products formulated in varying consistencies to suit conditions of pump ability in different centralized lubrication systems.
- Wide range operating temperature band of (-) 20°C to (+) 120°C.

Applications :

- Universal joints, geared motors, enclosed gear boxes with high loads.
- For general purpose ball, roller, needle roller, taper roller bearings and gears.
- Products ideally suited for centralized lubrication systems.

Characteristics	Test Method	Unit	MPG 1	MPG 0	MPG 00	MPG 000
Appearance	Visual	–	Smooth	Smooth Semi Fluid	Smooth Semi Fluid	Smooth Semi Fluid
Colour	Visual	–	Yellowish	Yellowish	Yellowish	Yellowish
Base [Thickener]	–	–	Lithium	Lithium	Lithium	Lithium
Base Oil	–	–	Mineral	Mineral	Mineral	Mineral
NLGI Grade	–	–	# 1	# 0	# 00	# 000
Worked Penetration	ASTM D-217	0.1mm	310 – 340	355 – 385	400 – 430	445 – 475
Operating Temperature Range	–	°C	-20/+120	-20/+120	-20/+120	-20/+120

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.7 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.