

### MPG-2 (Red)

*Lithium Complex Based Multifunctional  
High Temperature Extreme  
Pressure Greases*

#### Benefits :

- Excellent Shear Stability.
- Extreme pressure additives provide high load carrying capacity.
- Resist water washout.
- Long term lubrication for bearings.
- Provide adequate rust protection.
- Good pump ability.
- Wide range operating temperature band of (-) 20°C to (+) 160°C.

#### Applications :

- For general purpose ball, roller, taper roller and needle roller bearings.
- Suitable for bearings under heavy loads.
- For almost all types of industries.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Smooth
Colour	Visual	–	Red
Base [Thickener]	–	–	Lithium Complex
Base Oil	–	–	Mineral
NLGI Grade	–	–	# 2
Worked Penetration	ASTM D-217	0.1mm	265 – 295
Dropping Point	ASTM D-2265	°C	+ 240
Four Ball Welded Load	ASTM D-2596	N	2800
Water Washout @ 80°C, wt. loss	ASTM D-1264	%	< 5
Copper Strip Corrosion Test	ASTM D-4048	Rating	1a
Operating Temperature Range	–	°C	-20/+160

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice.  
This supersedes our previously issued data sheets.

[REV. 2 / 01.01.14 ]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.