

Technical Data Sheet

Spraylube 1250 RNG

Sprayable fluid grease for running-in of open gears

Benefits :

- Provides excellent resistance to extreme loads
- Improves conditions for running-in
- Reduces friction and wear and thereby minimizes maintenance costs.
- High Pumpability
- High adhesive properties.
- Does not contain lead or other heavy metals

Applications :

- This products has been developed for the running –in new gears or for the repairs of their damage surface (severe wear and/or other problem like pitting, scoring, spalling)
- This products does not contain abrasive partials.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	\sim	Semi fluid Grease
Colour	Visual		Black
Base [Thickener]	-	-	Aluminium Complex
Base Oil	-	-	Mineral
NLGI Grade			#00
Worked Penetration	ASTM D-4048	0.1 mm	400-430
Four Ball Weld Load	ASTM D-2596	N	> 6000
Lubricating film resistance temperature		O ₀	> 250
Solid Lubricants Type	-	-	Graphite, MoS ₂

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice This supersedes our previously issued data sheets.

[REV. 3 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA. Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com