

Ultratack Mill Grease 460

*High Viscosity Calcium Sulphonate
Grease for Steel & Paper Mills*

Benefits :

- Suitable over wide temperature range.
- Excellent water resistance.
- High load carrying capacity.
- Excellent shear stability.
- High drop point.
- Excellent anti-wear properties.
- Contains no lead or other harmful matter.

Applications :

- Work Roll & Backup roll bearings in steel mills.
- Heavily loaded bearings in paper mills which come in contact with water.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Soft, Smooth
Colour	Visual	–	Black
Base [Thickener]	-	-	Calcium Sulphonate
Base Oil	–	–	Mineral
Base Oil Viscosity @ 40°C	ASTM D-445	cSt	460
NLGI Grade	–	–	# 2
Worked Penetration	ASTM D-217	0.1 mm	265 - 295
Dropping Point	ASTM D-2265	°C	+ 280
Four ball Weld load	ASTM D-2596	N	5000
Copper Strip Corrosion Test	ASTM D-4048	rating	1a
Water Washout @ 80°C, wt. loss	ASTM D-1264	%	< 0.45
Roll Stability Change	ASTM D-1831	%	< 5
Operating Temperature Range	–	°C	- 20 / +150

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.5 /01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.