

## Ultratack Mill Grease SG 400

*High Performance High Load  
Coolant/Water Resistance Grease*

### Benefits :

- Excellent resistance to water washout.
- Good resistance to coolants even in mild acidic conditions.
- Withstands high loads and extreme pressures.
- Provides good protection against rust and corrosion.
- Tacky nature provides good adherence to metal substrates.
- Withstands high temperatures.
- Wide range operating temperature band of (-) 20 to (+) 180°C.
- Fortified with chosen anti-wear and anti-corrosion additives.
- Extends bearing lives.

### Applications :

- Ideally suited for cold Rolling mills / Paper mills.
- For medium to slow moving heavily loaded work roll & back up roll bearings.
- For heavy duty applications in agriculture, steel, rubber mills, paper mills, cement, chemical and many other industries.

Characteristics	Test Method	Unit	Specifications
Appearance / Colour	Visual	–	Smooth / Deep Brown
Base [Thickener]	–	–	Special Complex Soap
Base Oil	–	–	Mineral
Base Oil Viscosity @ 40°C	ASTM D-445	cSt	400 – 450
Flash Point (of Base Oil) [Min.]	ASTM D-92	°C	250
NLGI Grade	–	–	# 2
Worked Penetration	ASTM D-217	0.1 mm	265 – 295
Dropping Point	ASTM D-566	°C	+ 225
Four Ball Weld Load	ASTM D-2596	N	4500
Water Wash out @ 80°C, wt. loss	ASTM D-1264	%	< 1.5
Copper Strip Corrosion Test	ASTM D-4048	rating	1a
Operating Temperature Range	–	°C	-20/+180

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.3 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**Anand Engineers Pvt Ltd.** 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com