

## HVG 28/6

### High Performance Silicone Grease

#### Benefits :

- Tacky grease designed for specific applications.
- Non toxic food grade grease.
- Offers good resistance to solvents like Methanol, Isopropanol, Acetone, Methyl Ethyl Ketone, Diethylene Glycol, Ethanol and hot and cold water.
- Does not affect plastic or rubber parts.
- Strong adhesive sealant.
- None melting.
- Stable over wide range temperature band of (-) 40°C to (+) 260°C.

#### Applications :

- For lubrication of valves used in chemical industry and hot and cold water lines.
- Designed for sanitary fittings.
- As a lubricant for plastic and rubber parts.
- For lubrication and protection of O-rings, rubber seals and other rubber assemblies.
- For pneumatic equipments.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Translucent, tacky
Colour	Visual	–	White
Base [Thickener]	-	-	Non Soap
Base Oil	–	–	Silicone
NLGI Grade	–	–	# 2 / 1
Worked Penetration	ASTM D-217	0.1 mm	300 – 320
Dropping Point	ASTM D-2265	°C	None
Oil Separation @ 100°C, 24 hrs	*CTM	%	< 2
Operating Temperature Range	–	°C	-40/+260

\*CTM=Corporate Test Method

MSDS available on request.

Due to continual up gradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.5 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**Anand Engineers Pvt Ltd.** 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com