

HVG 7

***Mould Release Agent
For Plastic & Rubber Parts***

Benefits :

- Effective release agent for complex rubber and plastic moulds.
- Gives good surface finish to the product.
- Forms even coating to prevent attack of moisture, chemical fumes etc.
- Can easily be diluted with Trichloro Ethylene, Xylene and sprayed on moulds.
- Wide operating temperature range (-) 40°C to (+) 250°C.

Applications :

- As a mould release agent in plastic and rubber parts.
- In plywood and hard board industry as release agent and for preventing glue for fouling of machinery.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Translucent, tacky
Colour	Visual	–	White
Base [Thickener]	-	-	Non Soap
Base Oil	–	–	Silicone
NLGI Grade	–	–	#0
Worked Penetration	ASTM D-217	0.1 mm	355 – 385
Dropping Point	ASTM D-2265	°C	None
Operating Temperature Range	–	°C	-40/+250

*CTM=Corporate Test Method

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com