

ChainLube 150 & 460

High Performance Chain Oils

Benefits :

- High load carrying capacity.
- Good adherence to base metal.
- Excellent water resistant and demulsibility properties.
- Reduced tendency to foam.
- Protects metals against rust & corrosion.
- Ensures long life of chains due to good oxidation and thermal stability.
- Penetrates well inside the pins, rollers & bushes of the chain links.

Applications :

- Oils for Industrial chains, open gears, guides, plain and rolling element bearings, rolls, drives, sprockets, flexible couplings, employing manual, splash, circulation and spray lubrication systems.

Method of Use :

- By brush, dripping, spraying, splashing or circulation methods.
- To obtain good results, application on dry and clean surfaces is recommended

Characteristics	Test Method	Unit	ChainLube 150	ChainLube 460
Colour	Visual	-	Pale Yellow	Dark Brown
Density @ 27°C	*CTM	gm/cc	0.90 ± 0.05	0.90 ± 0.05
Viscosity @ 40°C	ASTM D-445	cSt	150 ± 15	460 ± 45
Flash Point [min.]	ASTM D-92	°C	230	230
Pour Point	ASTM D-97	°C	- 9	- 9
Copper Strip Corrosion Test	ASTM D-130	-	1a	1a
Operating Temperature Range	-	°C	- 7/+150	- 7/+150

*CTM=Corporate Test Method.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.7 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com