

Stenol 50 Plus

*Premium Grade Synthetic
High Temperature Chain Oil*

Benefits :

- Reduces wear and tear.
- Complete lubrication in hard to reach area due to excellent penetrating properties.
- Chain remains clean due to low residual formation and carbonization.
- Reduces re-lubrication period due to very low evaporation rate.
- Remains stable at high temperature.
- Operating temperature between 200°C to 250°C.

Applications :

- Conveyor chains operating under heavy loads and high temperatures.
- Slide ways and open bearings operating under high temperatures and heavy loads.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Clear Oil
Colour	Visual	–	Pale Yellow
Base Oil	–	–	Synthetic
Density @ 27°C [typ.]	*CTM	gms/cc	0.93 ± 0.05
Viscosity @ 40°C @ 100°C	ASTM D-445	cSt cSt	170 – 200 18 – 20
Flash Point [min.]	ASTM D-92	°C	270
Pour Point [min.]	ASTM D-97	°C	-15
Evaporation Loss @ 200°C for 16 hrs.	*CTM	%	< 5
Four Ball Wear Scar	ASTM D-2266	mm	0.4
Copper Strip Corrosion Test	ASTM D-130	–	1a
Operating Temperature	–	°C	(+) 250

*CTM=Corporate Test Method.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.5 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com