

Viscotack

Adhesive Chain Lubricating Oil

Benefits :

- Penetrates well, deep inside the frictional parts for lubrication.
- Minimizes wear and extends chain life.
- Protective coating formed over the surface does not get thrown off wide specs.
- Provides good resistance to hot and cold water and steam.
- Offers good protection against rust, water and sea water corrosion.
- Excellent lubrication properties even in difficult to reach areas.

Applications :

- For Industrial Chains operating under water steam, sea water, dusty & humid atmospheres.
- For long term lubrication of clutch / brake levers, pedals, gear drives, bearings, hinges, locks, roller chains for motorcycles, forklifts, mining vehicles.
- For lubrication of cables, wire ropes and spring assemblies.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Tacky Viscous Oil
Colour	Visual	–	Dark Brown
Density @ 27°C [typ.]	*CTM	gms/cc	0.85 ± 0.05
Flash Point	ASTM D-92	°C	+230
Four Ball Weld Load	ASTM D-2596	N	2000
Water Washout @ 80°C, wt. loss	ASTM D-1264	%	< 5
Copper Strip Corrosion Test	ASTM D-130	–	1a

*CTM=Corporate Test Method

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.3 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com