

## G-BesluxCaplex M 2 Atox

*USDA / NSF Certified,  
High Performance Food Grade Grease*

### Benefits :

- Odour free and non-toxic.
- Provides excellent water resistance.
- Can be used in bearings having speed factor = 5,00,000
- High sealing capacity and resistance to heavy loads.
- Meets European Standards and recommendations applied to raw material, as well as both the FDA & USDA Standards.
- **USDA Class H-1 lubricant.**
- Product approved by **NSF International.**

### Applications :

- For lubrication of bearings with wide range of speeds.
- For sealing machines.
- General lubrication of mechanism including valve stems, glands, plugs in pipe lines in food industry.
- As Food Grade lubricant in Food/ Pharmaceutical Industry wherever there may be an incidental contact between food and lubricant.
- As a protective anti-rust film.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Soft,Smooth
Colour	Visual	-	White
NLGI Grade	-	–	#2
Worked Penetration @ 25°C	ASTM D 217	0.1mm	265-295
Dropping point [min.]	ASTM D-2265	°C	250
DN Value [Speed factor]	–	–	5,00,000
Operating TemperatureRange	–	°C	-20/+140

Make : Brugarolas, Spain

Marginal variation in shade can be expected from batch to batch. The colour has no effect on the lubricating properties of the product.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.7 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.