

Graphol 2000

*A Colloidal Dispersion of Graphite
In Oil*

Benefits :

- Graphite coating reduces wear and therefore increases die life.
- Improves metal flow and gives excellent surface finish.
- Reduces working loads.
- Eases punch release thereby avoiding die damage and downtime.

Applications :

- Hammer forging die upsetting tools.
- Extrusion presses.
- Press.
- Closed die Forgings.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Smooth Oily Liquid
Colour	Visual	–	Black
Density @ 27°C [typ.]	*CTM	gms/cc	0.95 ± 0.05
Flash Point	ASTM D-92	–	+ 220
Solid Lubricant	–	–	Graphite

*CTM=Corporate Test Method

Important: Stir well before use.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com