

Technical Data Sheet

Graphol GFL 5000 Plus

A High performance Medium Density Graphite Based Die Lubricant for Hot & Warm Forging / Extrusion

Benefits :

- GFL 5000 Plus is water based, odorless and provides safe and comfortable working environment.
- Advance additive system of wetting and dispersing agent.
- Excellent metal flow.
- Smokeless and does not emit toxic fumes.
- It has chosen additives to reduce wear and tools corrosion.
- Extends die life. Non-toxic in nature.
- Evenly spreads on metal surface with high area coverage.
- Good high temperature stability and shear resistance.
- Excellent releasing does not leave scratches or stain on the forged component.
- Highly Economical.

Applications :

- Hot and Warm forging, Steel, Aluminum Copper Alloys and extrusion of these.
- Push Bench and Piercing Areas in Steel Pipe making.
- · Backward extrusion of steel in vertical presses.

Characteristics	Test Method	Unit	Specification
Appearance	Visual	-	Smooth Liquid
Color	Visual	-	Greyish Black
Specific Gravity @ 15°C	*CTM	-	1.1 <u>+</u> 0.05
Flash Point	ASTM D-92	°C	None
Fire Point	ASTM D-92	°C	None
pH Value	*CTM	_	8.5 – 9.5

*CTM= Corporate Test Method

Guidelines :

- Normal recommended dilution ratio with water is **1:10**. This may be altered depending on the intricacy of the extrusion/forging.
- Spray gun is most suitable for application.
- Product concentrate in the container shall be thoroughly stirred before dilution and preferably during operational use to avoid settling of solids, suggestively with low rpm propellers or other suitable modes.

Note: Suitable Dual Action Hand Spray Guns can be supplied on request.

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice This supersedes our previously issued data sheets.

[REV.1 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA. Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com