

Alkote

Bright Galva Coating Liquid

Benefits :

- Bright coating restores galvanized surfaces to their near original surface finish.
- Fast Drying.
- High purity aluminium enriched coatings.
- Easily sprayed with airless spray gun in hard to reach areas and hence can be applied 'in situ' positions without dismantling.
- Economic and wear resistant coating provides long lasting protection to ferrous surfaces and does not peel off like normal paints.
- Outstanding cathodic protection.
- Best suited for salty and humid environment.
- Heat resistant upto 600°C.
- Glossy finish offers aesthetic look to applied surfaces.

Applications :

- As a corrosion protector to exhaust pipes, manifolds motor vehicle silencers, pipes and other installation for air-conditioning plants, furnaces boilers, flanges.
- Product caters to needs of offshore rigs, power plants, chemical and fertilizer plants and bare metal surfaces.
- Re-treatment of galvanized or painted surfaces damaged by welding or mechanical abrasion.

Characteristics	Test Method	Unit	Specifications
Appearance	Visual	–	Uniform Liquid
Colour	Visual	–	Silver
Density @ 27°C [typ]	*CTM	gms/cc	1.0 ± 0.1
Film Type	Visual	–	Dry
Coating Thickness	*CTM	μ	5 – 7
Drying Time			
Touch Dry	Visual	minutes	10
Tack Free	Visual	minutes	30
Curing	Visual	hours	24

*CTM=Corporate Test Method.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.7 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

CONTROLLED COPY