

**Benefits :**

- Prevents slippage of belts.
- Eliminates squeaks and improves transmission.
- Removes oils, grease and glaze formation.
- Restores flexibility and suppleness of belts.
- Enhances belt grip.
- Improved power consumption due to less of belt slippage and better belt performance.
- Prolongs belt life.
- Eco friendly propellant promotes clean environment.

**Applications :**

- For all types of round, flat or V-belts made of rubber, leather, canvas and fabric.
- Belts used in compressors, generators, pumps, motors, conveyors, lathes and other machinery in practically all types of industries.

Characteristics	Test Method	Unit	Specifications
Colour	Visual	–	Colourless
Density @ 27°C	*CTM	gms/cc	0.80±0.02
Film Type	Visual	–	Wet tacky
Propellant	–	–	Non-CFC

\*CTM = Corporate Test Method.

Packing : 500 ml Aerosol can  
 Carton size : 10/25 Cans per carton

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
 This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

CONTROLLED COPY