

## Ecosil NS 2875

*High Performance Non Silicone  
Mould Release Spray*

### Benefits :

- Excellent penetration in hard to reach areas.
- Non-staining and non-corrosive.
- Especially formulated as a mould release for parts which are required to be painted.
- No peel off of paint.
- Improved finish.
- Low down time provides increased productivity.
- Ozone friendly propellant promotes clean environment.

### Applications :

- As a mould release agent for plastic components which are required to be painted.
- As an antisplatter for metal surface which require post weld painting.

Characteristics	Test Method	Unit	Specifications
Colour	Visual	–	Pale Yellow
Density @ 27°C [typ.]	*CTM	gms/cc	0.87±0.02
Propellant	–	–	Non-CFC

\*CTM = Corporate Test Method

Packing : 550 ml Aerosol can  
Carton size : 10/25 cans per carton

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.3 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**Anand Engineers Pvt Ltd.** 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com