

Ecosil Plus

High Performance Mould Release Spray

Benefits :

- As a mould release, it has excellent penetration in hard to reach areas.
- Contains extra silicone oil for improved performance.
- Provides excellent finish to molded components.
- Non-staining and non-corrosive.
- Does not harm plastics. Has mild fragrance.
- As an anti spatter it promotes quality welds due to non-build up of spatters.
- Eliminates need for hard chiselling and grinding after welding.
- Low downtime provides increased production efficiency.
- Ozone friendly propellant promotes clean environment.

Applications :

Mould Release

- All types of plastic injection moulding.

Anti Spatter

- Different types of weldings. Highly effective on MIG, TIG & SMAW welding processes.

General Purpose

- Superior lubricant for door & window hinges, metal locks, conveyors, springs and sliding surfaces.
- Wide range operating temperature band of (-) 40°C to (+) 250°C.

Characteristics	Test Method	Unit	Specifications
Colour	Visual	–	Colorless
Density @ 27°C [typ.]	*CTM	gms/cc	0.97±0.02
Propellant	–	–	Non-CFC

*CTM = Corporate Test Method

Packing : 550 ml Aerosol can
Carton size : 10/25 cans per carton

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.3 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com