

## KopaLube

### Copper Based Antiseize

#### Benefits :

- Excellent antiseize property with copper as solid lubricant.
- Prevents seizures at high temperature.
- Resists fresh and salt water corrosion.
- Anti wear and protects against seizures and stick-slip.
- Provides good lubrication to slow moving sliding or rotating parts.
- Easy to apply in hard to reach areas.
- Wide range operating temperature band of (-) 20°C to (+)1100°C.
- Eco friendly propellant.

#### Applications :

- As an antiseize on threaded bolts and nuts.
- For brake linkages in automotive.
- On sliding surfaces as an antiseize and anti wear.
- For bolts on injection moulding machines.
- On press fit components.

Characteristics	Test Method	Unit	Specifications
Color	Visual	–	Copper
Density @ 27°C [typ.]	*CTM	gms/cc	1.0±0.1
Average Film Thickness	*CTM	μ	90 – 100
Film type	–	–	Wet
Solid Lubricant	–	–	Copper
Propellant	–	–	Non CFC

\*CTM=Corporate Test Method

Packing : 500 ml Aerosol can  
Carton Size : 10/25 cans per carton

**Method of use :** For effective spraying shake the Can vigorously for at least a minute before use. Spray from a distance of 6" to 8" inches from the object.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice  
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**Anand Engineers Pvt Ltd.** 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com