

Neverust 30

Dry Waxy Film Corrosion Protector

Benefits :

- A long term indoor / outdoor corrosion inhibitor.
- Waxy film seals out moisture completely.
- Non-reactive to rubber, plastic or painted surfaces.
- Long term protection (upto 1 year indoor) for all metals during shipment or extended storage.
- Can be easily removed with common cleansor solvents.
- Ozone friendly propellant promotes clean environment.

Applications :

- Machined surfaces and assemblies subject to long periods of storage or adverse shipping conditions.
- Equipments storage, cable and sealer, valves, pipe fittings, long term spare parts storage, armature storage, dies, moulds, cutting tools, motors, shafts.
- Protection of all equipment subject to heat, humidity, chemicals or severe corrosive atmospheres.

Method of use :

- Shake can well before use.
- The surface to be treated should be thoroughly cleaned, degreased and dried before application.
- For best result keep the Aerosol Can 8" to 10" away form the job at the time of spraying.

Characteristics	Test Method	Unit	Neverust 30 (Blue)	Neverust 30 (Clear)
Colour	Visual	–	Blue	Brownish
Density @ 27°C [typ.]	*CTM	gms/cc	0.83+0.02	0.83+0.02
Film Type	Visual	–	Dry Waxy	Dry Waxy
Average Film Thickness	*CTM	μ	3 – 4	3 – 4
Drying Time				
Touch Dry	Visual	minutes	10	10
Tack Free	Visual	minutes	30	30
Salt Spray Corrosion Test (passes)	ASTM B-117	hrs.	>=200	>=200
Propellant	–	–	Non-CFC	Non-CFC

*CTM=Corporate Test Method

Packing : 500 ml Aerosol can
Carton Size : 10/25 cans per carton

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice.
This supersedes our previously issued data sheets.

[REV.4 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.