

Peelkote

Peelable Protective Coating

Benefits :

- Protects against scratches & stains.
- Seals away moisture and air thereby preventing oxidation, tarnishing and damage during storage and shipment.
- Provides long term protection against rust, corrosion and abrasion during shipment.
- Requires no additional solvent for cleaning and removal.
- Can be easily 'peeled off' from any of the edges without damage to the substrate.
- Protects against contamination due to paint spray, dirt & dust.
- Can be easily sprayed on various metals and most painted surfaces.
- Ozone friendly propellant promotes clean environment.

Applications :

- Precision tools, components, gauges, dies, moulds, spare parts and other store items.
- Machined surfaces, control panels, metal laminates, anodized sections.
- On aluminium doors & windows, decorative laminates and metal labels as protective coating before installation.

Characteristics	Test Method	Unit	Specifications
Color	Visual	–	Clear / Blue
Density @ 27°C [typ.]	*CTM	gms/cc	0.83±0.02
Film Appearance	Visual	–	Uniform Dry Peelable
Drying Time			
Touch Dry	Visual	minutes	10
Tack Free	Visual	minutes	30
Film Thickness	Visual	micron	22-27
Propellant	–	–	Non-CFC

*CTM=Corporate Test Method

Packing : 500 ml Aerosol can
Carton Size : 10/25 cans per carton

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.