

Plastolube

Lubricant Spray for Metals & Polymers

Benefits :-

- Long life lubrication.
- Most suited for plastic to plastic and plastic to metal substrates.
- For moderate movements and light loads
- Compatible with most plastics and elastomers due to chosen oil blend.
- Guards against corrosion
- Chosen additives to give maximum performance.
- Good adhesion to material substrate.
- Exhibits good dampening properties.
- Plastolube is a silicone free synthetic lubricant.
- Eco-friendly propellant.

Applications :-

- To lubricate metal-to-metal or plastics-to-plastics sliding movements.
- To reduce friction and wear on mechanisms and to protect these from stick slip.
- For lubrication of frictional partners with metal to plastic or plastic to plastic contact.
- To lubricate sliding area like joints, linkages, lever, guide ways & machine parts of transport systems, packaging & automatic filling machines.
- Lubrication of air vent assemblies in automobiles.

Characteristics	Test Method	Unit	Specifications
Colour	Visual	-	Whitish
Film Type	Visual	-	Tacky
Density @ RT	*CTM	gms /cc	0.80±0.02
Propellant	-	-	Non CFC

*CTM=Corporate Test Method.

Packing : 500 ml. Aerosol can.
Carton size : 10 /25 cans per carton.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV. 1 / 16.08.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

Anand Engineers Pvt Ltd. 66, MIDC, Road No. 13, Andheri (East), Mumbai - 400093,INDIA.

Tel :+91 22 28219292/8/9 Fax: +91 22 28379337 Email: sales@molygraph.com Web: www.molygraph.com