

Viscotack

Adhesive Chain Lubricant

Benefits :

- Penetrates well, deep inside the frictional parts for lubrication.
- Minimizes wear and extends chain life.
- Protective coating formed over the surface does not get thrown off wide specs.
- Provides good resistance to hot and cold water and steam.
- Offers good protection against rust, water and sea water corrosion.
- Excellent lubrication properties even in difficult to reach areas.

Applications :

- For Industrial Chains operating under water steam, sea water, dusty & humid atmospheres.
- For long term lubrication of clutch / brake levers, pedals, gear drives, bearings, hinges, locks, roller chains for motorcycles, forklifts, mining vehicles.
- For lubrication of cables, wire ropes and spring assemblies.

Characteristics	Test Method	Unit	Specifications
Colour	Visual	–	Amber
Density @ 27°C [typ.]	*CTM	gms/cc	0.82±0.02
Film Type	Visual	–	Oily tacky
Four Ball Weld Load	ASTM D-2596	N	2000
Water Washout @ 80°C, wt. loss	ASTM D-1264	%	< 5
Copper Strip Corrosion Test	ASTM D-130	–	1a
Propellant	–	–	Non-CFC

*CTM = Corporate Test Method

Packing : 500 ml Aerosol can (with extension tube)
Carton Size : 10/25 cans per carton

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.7 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

CONTROLLED COPY