

Zinckote

**Zinc Based Cold Galvanizing
Corrosion Protector**

Benefits :

- High purity zinc enriched coating.
- High adhesion on substrate materials.
- Actively fights against rust and corrosion.
- Protects structures and material from Sea Water Corrosion.
- Provides excellent cathodic protection.
- Zinc acts as the sacrificing material thereby protecting the base material even when scratched or abraded.
- Replaces commonly used 'injurious to health' paints.

Applications :

- For equipment and installations exposed to corrosive atmosphere.
- Transmission towers, trailers, storage tanks, metal roofs on the underground distribution.
- Chemical Plants, Power Plants, exhaust pipes, ducting, wire fences, bar gates, road signs, traffic light posts, ramps and various other types of steel construction.

Characteristics	Test Method	Unit	Specifications
Color	Visual	-	Silver Grey
Density @ 27°C	*CTM	gms/cc	0.80±0.05
Film Type	Visual	-	Dry
Avg. Coating Thickness	*CTM	micron	7 – 10
Avg. Surface Area Coverage [per can]	*CTM	sq.m.	2.0 - 2.5
Drying Time : Touch Dry	Visual	minutes	10
Tack Free	Visual	minutes	30
Curing	Visual	hours	24
Propellant	-	-	Non CFC

*CTM=Corporate Test Method

Packing : 500 ml Aerosol can
Carton Size : 10/25 cans per carton

Method of use : For effective spraying shake the Can vigorously for at least a minute before use. Spray from a distance of 6" to 8" inches from the object.

MSDS available on request.

Due to continual upgradation of products above data is subject to change without notice
This supersedes our previously issued data sheets.

[REV.6 / 01.01.14]

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

CONTROLLED COPY