

Auto G 15 H Series

Lithium based silicone grease fortified with PTFE for added lubricity & performance



YOUR BENEFITS

- Product designed for maximum benefits for control cables.
- Excellent compatibility with most plastics and elastomers.
- PTFE provides good anti-wear and low noise properties and added lubricity.
- Good water resistance property.
- Low oil separation.
- Withstands shearing force and no carbonization on prolong use due to high temperature.
- Contains no heavy metals or hazardous substances.
- Good brushability.

APPLICATION

- For control cables in automotive like parking, brakes, hood, doors etc.

CHARACTERISTICS	TEST METHOD	UNIT	AUTO G 15 H1 F	AUTO G 15 H0 F
Appearance	Visual	-	Smooth	Smooth
Colour	Visual	-	White	White
Base [Thickener]	-	-	Lithium	Lithium
Base Oil	-	-	Silicone	Silicone
Base Oil Viscosity @25°C	ASTM D 4878	cSt	500	500
NLGI Grade	-	-	#1	#0
Worked Penetration	ASTM D 217	0.1 mm	310 - 340	355 - 385
Dropping Point	ASTM D 2265	°C	+ 220	+ 220
Operating Temperature Range	-	°C	-40/+200	-40/+200

INDUSTRY:

Automotive
Components

PACK SIZE:

20 kg Bucket
180 kg Drum

SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

