

HVG 7

Mould Release Agent For Plastic and Rubber Parts



YOUR BENEFITS

- Effective release agent for complex rubber and plastic moulds.
- Gives good surface finish to the product.
- Forms even coating to prevent attack of moisture, chemical fumes etc.
- Can easily be diluted with Trichloro Ethylene, Xylene and sprayed on moulds.
- Wide operating temperature range (-) 40°C to (+) 260°C.

APPLICATION

- As a mould release agent in plastic and rubber parts.
- In plywood and hard board industry as release agent and for preventing glue for fouling of machinery.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Soft, tacky
Colour	Visual	-	Translucent White
Base [Thickener]	-	-	Non Soap
Base Oil	-	-	Silicone
NLGI Grade	-	-	#1
Worked Penetration	ASTM D 217	0.1 mm	310-340
Dropping Point	ASTM D 2265	°C	None
Operating Temperature Range	-	°C	-40/+260

INDUSTRY:

Plastic Moulding

PACK SIZE:

1 Kg / 5 Kg / 20 kg Bucket

SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

