

# Long Life 2 Plus

High Temperature Heavy Duty Long Life Premium Grease



## YOUR BENEFITS

- Capable of carrying high loads.
- High base oil viscosity.
- Extended re-lubrication periods.
- Guards against corrosion.
- High adhesion to metal substrate.
- Fortified with solid lubricants.
- Moisture resistant.
- Wide range operating Temperature Band.
- Resists fretting corrosion and brineling.

## APPLICATION

- For high load & slow to medium-fast movements metal to metal lubrication.
- For lubrication of various types of anti-friction bearings.
- Earth moving equipment, conveyors, cables, tractors, trucks, transportation equipment and material handling systems.
- Universal joints, splined shafts, and sliding mechanism.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance / Colour	Visual	-	Smooth / Black
Base [Thickener]	-	-	Special Complex
Base Oil	-	-	Mineral
Base Oil Viscosity @40°C	ASTM D 445	cSt	400
NLGI Grade	-	-	#2
Worked penetration @25°C	ASTM D 217	0.1 mm	265 – 295
Dropping Point	ASTM D 2265	°C	+250
Water Washout @80°C, wt. loss	ASTM D 1264	%	< 5
Four Ball Weld Load	ASTM D 2596	Kgs	315
Four Ball Wear Scar	ASTM D 2266	mm	0.6
Operating Temperature Range	-	°C	-20/+220

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice. This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

### INDUSTRY:

MRO

### PACK SIZE:

1 Kg / 5 Kg / 20 kg Bucket  
180 kg Drum

### SHELF LIFE:

24 Months

